

Drilling tutorial

Fluids management

Parameters for Drilling Fluids

- Density of drilling mud keep under 9lbs /gal
- Grout density- same coming out of the hole as leaving the grouter +/- .2 lbs/gal



Fluid Control

- Soda Ash- $\frac{1}{4}$ - $\frac{3}{4}$ lb per 100 gallons of mud
- Bentonite mixed for estimated borehole volumes
- Polymers for filtrate control $\frac{1}{4}$ - $\frac{3}{4}$ lbs per 100 gallons of mud
- Viscosity maintained below 40 second mud.



Fluid Properties

- Keep entrained sand content kept below 2.5-3%
- Higher sand content raised Density (weight)
- Increase fluid loss to formation(Filtrate)
- Compromises wall cake



Solids control



Fluids control

Wall Cake & Filtrate



Filter Press

- Rate of fluid loss



Fluids control Cont.

- Make up water
- drilling fluid/grout slurries
- pH monitored 8.5-9.5
- Calcium < 100 PPM
- Chlorides < 500 PPM
- Chlorine < 50 PPM



Fluid control Cont..

- Supplemental drilling fluid reserve...
- Use when refilling pit-
fresh water degrade
fluid properties.
- Mud Viscosity- 32-38
sec per quart
- Clear Water Viscosity-
26 sec per quart

